

Gauge Valves and Instrument Manifolds

GV, GR Series

2-valve, 3-valve and 5-valve Manifold Series



FITOK Group

FITOK GmbH (Headquarter)

Sprendlinger Landstr. 115, 63069 Offenbach, Germany
Tel.: +49 69 8900 4498
Fax: +49 69 8900 4495

FITOK INC

13000 Murphy Road, Suite 116, Stafford, TX 77477, USA
Tel.: +1 281 888 0077
Fax: +1 281 247 1806

FITOK INCORPORATED

Yingtailong Industrial Park, Shenzhen, 518109, China
Tel.: +86 755 2803 2500
Fax: +86 755 2803 2619

info@fitokgroup.com
www.fitokgroup.com

FI15040813

FITOK
Valves and Fittings

www.fitokgroup.com

Contents

Gauge Valves
GV Series and GR Series



01

Instrument Manifolds
2-valve Manifolds



3-valve Manifolds



5-valve Manifolds and C Integral Manifolds



05


The Auxiliary Installation for Manifolds and Transmitters of Different Brands
Rosemount, EJA, Honeywell and SIEMENS Transmitters

18

Gauge Valves
GV Series and GR Series

Features


- Maximum working pressure:
Stainless steel: up to 6000 psig (414 bar)
Alloy 400: up to 5000 psig (345 bar)
- GV series working temperature:
PTFE packing: -65°F to 450°F (-54°C to 232°C)
Graphite packing: -65°F to 1200°F (-54°C to 649°C)
- GR series working temperature:
Acetal seat: -20°F to 250°F (-28°C to 121°C)
PEEK seat: -20°F to 400°F (-28°C to 204°C)
PFA seat: -20°F to 400°F (-28°C to 204°C)
- Non-rotating lower stem, ball tip and plug tip designs
- Variety of materials for seat and packing
- Safety back seating seals in fully open position
- Rolled spindle operating threads
- Lubricant for stem thread isolated from the media
- Externally adjustable gland
- Bonnet locking pin fitted as standard
- Low torque operating T bar handle
- Handle of different colors available for option
- Steady and durable fastening of the handle by double lock-pins
- Leak-tight performance testing for every valve with nitrogen at the maximum working pressure



Standard Materials of Construction


Item	Part	Valve Body Material		
		316 SS	Alloy 400	NACE MR0175
1	Handle	Anodized aluminum		
2	Set Screw	Nickel cadmium-plated steel		
3	Packing Bolt	321 SS/A276		
4	Upper Stem	316 SS/A276		
5	Lock Nut	316 SS/B783		
6	Bonnet	316 SS/A479	Alloy R-405/B164	Annealed 316 SS/A479
7	Gland	316 SS/A276		
8	Packing	PTFE or graphite		
9	Lock Pin	304 SS/A276		
10	Lower Stem	Chrome-plated 316 SS/A276	Alloy R-405/B164	Alloy R-405/B164
11	Body	316 SS/A479 316 SS/A182	Alloy 400/B164, B127,B564	Annealed 316 SS/A479
12	Seat	Acetal or PEEK or PFA		
Lubricant		Molybdenum disulfide-based		

Process interface valves for sour gas service are available. Materials are selected in accordance with NACE MR0175/ISO 15156. Contact the authorized representative or FITOK Group if any request.



Ball Tip Design Valves


Pressure vs. Temperature



Based on PEEK stem packing.

Plug Tip Design Valves

Pressure vs. Temperature





- 1. Rating limited to 250°F (121°C) max. with acetal seat material, not recommended for temperature higher than 200°F (93°C) for water and steam application.
- 2. Based on PEEK seat and graphite stem packing.

Types and Dimensions



Standard Type

Basic Ordering Number	Design	Inlet/Process	Outlet/Instrument	Test/Vent/Plug
GV□□-NS8-FNS8	Ball Tip	1/2 Male NPT	1/2 Female NPT	1/2 Female NPT
GR□□-NS8-FNS8	Plug Tip			
GV□□-NS12-FNS12	Ball Tip	3/4 Male NPT	3/4 Female NPT	1/2 Female NPT
GR□□-NS12-FNS12	Plug Tip			



Lagging Extension Body Type



Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent/Plug
GV□□-NS8-FNS8-E	1/2 Male NPT	1/2 Female NPT	1/2 Female NPT
GR□□-NS8-FNS8-E			



Lagging extension body is inserted through pipe for insulation.

Miniature Type

Basic Ordering Number	Inlet/Process	Outlet/Instrument
GV□□-NS8-FNS8-C	1/2 Male NPT	1/2 Female NPT
GR□□-NS8-FNS8-C		



GRSS—NS8—FNS8—CPW—GR—SF2									
Series	Body Material	Inlet Type	Inlet Size	Outlet Type	Body Style	Seal Material	Tip Material	Packing Material	Handle
GV Ball Tip Design	SS 316 SS	FNS Female NPT	8 1/2"	Same as Inlet	Standard Type	Same as Body	Same as Body	PTFE	Black Aluminum Bar
GR Plug Tip Design	6L 316L SS	NS Male NPT	12 3/4"	Specify in the same way as inlet type and size	Miniature Type	1 Stellite	W Stellite	G Graphite	Red Aluminum Bar
	S4 304 SS	FRT Female BSPT	20 M20 x 1.5		C Type	Acetal	D5 Duplex 2205		
	4L 304L SS	RT Male BSPT			E Type	P PEEK	TI Titanium Gr.4	PTFE	
	S1 321 SS					F PFA	A20 Alloy 20		
	D5 Duplex 2205	FMS Female Metric Thread (for RP)					INC Alloy 600		321 Stainless Steel Bar
	TI Titanium Gr.4	MS Male Metric Thread (for RG)					HC Alloy C-276		
	A20 Alloy 20	FRP Female BSPP (for RP)							Black Knob
	M Alloy 400								
	INC Alloy 600								
	HC Alloy C-276								
	B Brass								
	CS Carbon Steel								
	904L 904L SS								
		Special Application		Cleaning and Packaging					
		NO		FC-01					
		NACE S		F2					
		MIR0175							


Cleaning and Packaging:
FC-01: Standard cleaning and packaging for general industrial procedures.
FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleanliness requirement as stated in ASTM G93 Level C.

Instrument Manifolds


General Information

Features

- Maximum working pressure:
Stainless steel: up to 6000 psig (414 bar)
Alloy C-276: up to 6000 psig (414 bar)
Alloy 400: up to 5000 psig (345 bar)
- Working temperature:
PTFE packing: -65°F to 450°F (-54°C to 232°C)
Graphite packing: -65°F to 1200°F (-54°C to 649°C)
- Orifice: 0.157" (4.0 mm), CV: 0.35
- Two-stem design: thread hardened upper stem and smooth surface hardened lower stem
- Upper stem thread lubricant isolated from system media
- Linearly instead of helical movement of the nonrotating lower stem, avoiding galling damage to the seat and tip, as well as reducing the total friction area between the packing and the lower stem
- Safety back seating seals in fully open position
- Steady and durable fastening of the handle by double lock-pins
- Leak-tight performance testing for every valve with nitrogen at the maximum working pressure




Pressure vs. Temperature



1. Based on graphite stem packing.
2. Contact the authorized representative or FITOK Group for curve graph of other materials.

Standard Materials of Construction

Item	Part	Valve Body Material		
		316 SS	Alloy 400	Alloy C-276
1	Handle	Anodized aluminum		
2	Set Screw	Nickel cadmium-plated steel		
3	Packing Bolt	321 SS/A276		
4	Upper Stem	316 SS/A276		
5	Lock Nut	316 SS/B783		
6	Bonnet	316 SS/A479	Alloy R-405/B164	Alloy C-276/B574
7	Gland	316 SS/A276		
8	Packing	PTFE or PEEK or graphite		
9	Lock Pin	304 SS/A276		
10	Lower Stem	Chrome-plated 316 SS/A276	Alloy R-405/B164	Alloy C-276/B574
11	Body	316 SS/A479 316 SS/A182	Alloy 400/B164, B127,B564	Alloy C-276/B564
Lubricant		Molybdenum disulfide-based		



Handle color codes for functions:
BLACK=Isolate/block
RED=Test/vent
GREEN=Equalize

Process interface valves for sour gas service are available. Materials are selected in accordance with NACE MR0175/ISO 15150. Contact the authorized representative or FITOK Group if any request.


Instrument Manifolds

- Instrument manifolds are manufactured in accordance with ANSI B31.1 and B31.3, specifications meet MSS-SP-105. Flange design meets the requirements of MSS SP-99.
- 2-valve manifold are used with pressure gauges or pressure transmitters.
- 3-valve and 5-valve manifold are used with differential pressure transmitters.

2-valve Manifolds


Consist of one block valve and one bleed valve

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
2D□□-FNS8-A	1/2 Female NPT	Flanged	1/4 Female NPT




Every manifold is supplied with one PTFE sealing ring for manifold-to-instrument and four 7/16" UNF x 1.75" high tensile bolts.

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
2D□□-FNS8-L	1/2 Female NPT	Flange	1/4 Female NPT




Every manifold is supplied with one PTFE sealing ring for manifold-to-instrument and two 7/16" UNF x 1.75" high tensile bolts.

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
2D□□-FNS8-H	1/2 Female NPT	Flange	1/4 Female NPT




Every manifold is supplied with one PTFE sealing ring for manifold-to-instrument and two 7/16" UNF x 1.75" high tensile bolts.

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
2D□□-F-H	Flange	Flange	1/4 Female NPT




Every manifold is supplied with one PTFE sealing ring for manifold-to-instrument and two 7/16" UNF x 1.75" high tensile bolts.


Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
2R □ □ -FNS4-A	1/4 Female NPT	1/4 Female NPT	1/4 Female NPT




Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
2R □ □ -FNS4-C	1/4 Female NPT	1/4 Female NPT	1/4 Female NPT




Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
2R □ □ -FNS8-L	1/2 Female NPT	1/2 Female NPT	1/4 Female NPT



Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
2R □ □ -FNS8-NS8-H	1/2 Female NPT	1/2 Male NPT	1/4 Female NPT
2R □ □ -NS8-H	1/2 Male NPT	1/2 Male NPT	1/4 Female NPT




Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
2R □ □ -FNS8-V	1/2 Female NPT	1/2 Female NPT	1/4 Female NPT



3-valve Manifolds


Consist of two block valves and one equalizer valve

Basic Ordering Number	Inlet/Process	Outlet/Instrument
3D□□-FNS8-A	1/2 Female NPT	Flange
3D□□-FL8-A	1/2" FITOK	Flange




Every manifold is supplied with two PTFE sealing rings manifold-to-instrument and four 7/16" UNF x 1.75" high tensile bolts.

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
3D□□-FNS8-L	1/2 Female NPT	Flange	Optional
3D□□-FL8-L	1/2" FITOK	Flange	Optional



Every manifold is supplied with two PTFE sealing rings for manifold-to-instrument and four 7/16" UNF x 1.75" high tensile bolts.

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
3R□□-FNS8-V	1/2 Female NPT	1/2 Female NPT	Optional
3R□□-FL8-V	1/2" FITOK	1/2" FITOK	Optional




5-valve Manifolds

Double-bleed Function of 5-valve Manifold


Consist of two block valves, two bleed valves, and one equalizer valve

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
5D□□-FNS8-A	1/2 Female NPT	Flange	1/4 Female NPT
5D□□-FL8-A	1/2" FITOK	Flange	1/4 Female NPT



Every manifold is supplied with two PTFE sealing rings for manifold-to-instrument and four 7/16" UNF x 1.75" high tensile bolts.


Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
5R□□-FNS8-L	1/2 Female NPT	1/2 Female NPT	1/4 Female NPT
5R□□-FL8-FNS8-L	1/2" FITOK	1/2 Female NPT	1/4 Female NPT



5-valve Custody Transfer/Fiscal Metering Manifold


Consist of two block valves, one bleed valve, and two equalizer valves

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Vent	Test
5D□□-FNS8-B	1/2 Female NPT	Flanged	1/4 Female NPT	Optional
5D□□-FL8-B	1/2" FITOK	Flanged	1/4 Female NPT	Optional



Every manifold is supplied with two PTFE sealing rings for manifold-to-instrument and four 7/16" UNF x 1.75" high tensile bolts.

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Vent	Test
5R□□-FNS8-B	1/2 Female NPT	1/2 Female NPT	1/4 Female NPT	Optional
5R□□-FL8-FNS8-B	1/2" FITOK	1/2 Female NPT	1/4 Female NPT	Optional




C Integral Manifolds

This section is presently characterized by manifold designed specifically for Rosemount® coplanar™ pressure transmitters including the model 3051C, model 3051P, model 2024 and the model 3095. Each of the following manifold contains four 7/16" UNF x 1.75" high tensile bolts.


2-valve Manifold

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
2D□□-FNS8-C	1/2 Female NPT	Flanged	1/4 Female NPT




3-valve Manifold

Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
3D□□-FNS8-C	1/2 Female NPT	Flange	Optional
3D□□-FL8-C	1/2" FITOK	Flange	Optional



5-valve Manifold


Basic Ordering Number	Inlet/Process	Outlet/Instrument	Test/Vent
5D□□-FNS8-C	1/2 Female NPT	Flange	1/4 Female NPT
5D□□-FL8-C	1/2" FITOK	Flange	1/4 Female NPT



Manifold Bracket Supports


SS-M2P-2BK

- 1. The integral assembly including: bracket, U-bolts, bolts, gaskets, nuts
- 2. Used to fix 2R□□-XX-A, 2R□□-XX-C, 2R□□-XX-L, 2R□□-XX-V




SS-M2P-4BK

- 1. Install support design is available for horizontal or vertical installation
- 2. The integral assembly including: bracket, U-bolts, bolts, gaskets, nuts
- 3. Used to fix 2D□□-XX-A, 2D□□-XX-L, 2D□□-XX-H, 3D□□-XX-A, 3D□□-XX-L, 5D□□-XX-A, 5D□□-XX-B, 5R□□-XX-L, 5R□□-XX-B




SS-M2P-6BK

- 1. The integral assembly including: bracket, U-bolts, bolts, gaskets, nuts
- 2. Used to fix 2D□□-XX-C, 3D□□-XX-C, 5D□□-XX-C



SS-M2P-8BK

- 1. Install support design is available for horizontal or vertical installation
- 2. The integral assembly including: bracket, U-bolts, bolts, gaskets, nuts
- 3. Used to fix 2D□□-XX-A, 2D□□-XX-L, 2D□□-XX-H, 2D□□-XX-V, 3D□□-XX-A, 3D□□-XX-L, 5D□□-XX-A, 5D□□-XX-B



For more installation information regarding other manifolds, please contact the authorized representative or FITOK Group.

Ordering Information

3DSS—FNS8—LG—TY1S—SF2																
Manifold Series	Mount Type	Body Material	Inlet Type	Inlet Size	Outlet Type	Outlet Size	Body Style	Packing Sealing Material	Test Ports & Plugs	Mounting Bracket	For direct mount only		Special Application	Cleaning and Packaging		
											Flange Fasteners	Bolt Material	Flange Outlet Centerline			
2 2-valve	D Direct Mount	SS 316 SS	FNS Female NPT	4 1/4"	D type: Flanged R type: Same as Inlet Specified in the same way as the inlet type and size	4 1/4"	A Angle Pattern	PTE	No	No	7/16 - 20 UNF x 1.75"	7/16 - 20 UNF x 1.75"	2.125" (54 mm)	NO	FC-01	
3 3-valve	R Remote Mount	6L 316L SS	FRT Female BSPT	6 3/8" or 6 mm		6 3/8" or 6 mm	B Double equalize Function	G Graphite	1/4 Female NPT with Relief Valve	Y Yes	1 7/16 - 20 UNF x 3"	1 7/16 - 20 UNF x 3"	2.188" (55.6 mm)	S NACE MR0175	FC-02	
5 5-valve		S4 304 SS	ML Metric Tube Fitting	8 1/2" or 8 mm		8 1/2" or 8 mm	C Compact Pattern		1/4 Female NPT with Plug		2 M10 x 40 mm	2 M10 x 40 mm	2.250" (57.2 mm)		F2	
		4L 304L SS	FL Fractional Tube Fitting	10 10 mm			L Valves In-Line Mounted				3 M12 x 40 mm	3 M12 x 40 mm				
		S1 321 SS	FMS Female Metric Thread (for RP)	12 3/4" or 12 mm			H Valves Horizontally Mounted									
		D5 Duplex 2205	UMB Nut+Gasket +Metric Bulge Nipple	14 14 mm			V Valves Vertically Mounted									
		T1 Titanium Gr. 4	F Flanged	16 16 mm												
		A20 Alloy 20		20 M20 x 1.5												
		M Alloy 400														
		INC Alloy 600														
		HC Alloy C-276														
		B Brass														
		CS Carbon Steel														
		904L 904L SS														

- 1. The standard center line distance of direct mounting flange outlet of 3-valve manifold and 5-valve manifold is 2.125" (54 mm). Center line distance of 2.188" (55.6 mm) is suitable for range 6 and 7, 1151 series transmitter.
- 2. Center line distance of 2.250" (57.2 mm) is suitable for range 8, 1151 series transmitter. The standard configuration of direct mounting manifold contains PTFE flange seal ring and 7/16-20 UNF X 1.75" high tensile bolts, can be connected with transmitters under main brands, such as EJA, Honeywell, Foxboro 843 dlp, and Rosemount® 151, 2024, 3051H series.
- 3. 7/16-20 UNF x 3" high tensile bolts can be supplied, can be used for Rosemount® 3051C transmitter with process flange and coplanar mounting manifold.
- 4. Cleaning and Packaging:
FC-01: Standard cleaning and packaging for general industrial procedures.
FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleanliness requirement as stated in ASTM G93 Level C.


Accessories

Kidney Flange and Eccentric Flange


Features

- Working temperature :
PTFE: -65°F to 450°F (-54°C to 232°C)
Graphite: -65°F to 1000°F (-54°C to 538°C)
- Integral forged body
- Standard material: A182 F316

Kidney Flange



Eccentric Flange



The process connection type of transmitter can be transformed to other connection types.

Ordering Information

Basic Ordering Number	Connection Type and Size	Dimension in. (mm)
		A
SS-KF-FNS4	1/4 Female NPT	1.1 (28)
SS-KF-FNS8	1/2 Female NPT	1.1 (28)
SS-KF-FL8	1/2" FITOK	2.48 (63)
SS-KF-PB8	1/2 PB	2.1 (53.3)

A kidney flange set contains a PTFE flange seal ring and two 7/16 - 20 UNF high tensile bolts.

The Selection of Flange Seal Materials


The standard flange seal material is PTFE, graphite is an option, to order graphite flange seal material, add - G as a suffix.

Ordering Information

Basic Ordering Number	Connection Type and Size	Dimension in. (mm)
		A
SS-EF-FNS4	1/4 Female NPT	1.1 (28)
SS-EF-FNS8	1/2 Female NPT	1.1 (28)
SS-EF-FL8	1/2" FITOK	2.48 (63)
SS-EF-PB8	1/2 PB	2.1 (53.3)

- Eccentric flange needs to be ordered in whole set.
- A whole eccentric flange set contains two eccentric flanges, two PTFE flange seal rings and four 7/16 - 20 UNF high tensile bolts.


Various Combinations of Eccentric Flange Set



Combinations of eccentric flange set can give different center line distances of 2.0" (50.8 mm) , 2.125" (54 mm) and 2.25" (57 mm).


Relief Valve

- RB series RBSS-NS4 Bleed Valve is used as standard test/vent valve.
- For more information, refer to FITOK Bleed Valve RB series.



Calibration Fitting

- The calibration fittings can be connected directly with the bleed port of transmitter so that the calibration process can be simplified.
- For more information, refer to FITOK Calibration Fitting.



The auxiliary installation for manifolds and transmitters of different brands

Model of FITOK Manifolds Model of Transmitters	3(5)DXX-XX-X	3(5)RXX-FXXX-X	2DXX-XXX-X	2RXX-FXXX-X
Rosemount Transmitters				
3051 CD X X 2 (3, 4, 5, 7, 8) X X X X	A4			
3051 CD X X 0 X X X X H2 (H3, H4, H7, HJ)	A1			
3051 CD X X 0 X X X X HK	A2			
3051 CD X X 0 X X X X HL	A3			
3051 CD X X 0 X X X X DF	A5	A		
3051 CG (CA) X X 2 (3, 4, 5, 7, 8) X X X X			A4	
3051 CG (CA) X X 0 X X X X H2 (H3, H4, H7, HJ)			A1	
3051 CG (CA) X X 0 X X X X HK			A2	
3051 CG (CA) X X 0 X X X X HL			A3	
3051 CG (CA) X X 0 X X X X DF			A5	A
1151 D (H) P 3 (4, 5) X XX XX	A1			
1151 A (G) P 3 (4, 5) X XX XX			A1	
1151 D (H) P X X XX XX DF	A5	A		
EJA Transmitters				
EJA1X0A-XXX0 (5) X-XXXX	A1			
EJA1X0A-XXX1 (2, 3, 4) X-XXXX	A5	A		
EJA3 (4, 5) X0A-XXX0 (5)X-XXXX			A1	
EJA3 (4, 5) X0A-XXX1 (2,3,4)X-XXXX			A5	A
Honeywell Transmitters				
STDXX-XXA-XXX	A1			
STDXX-XXH-XXX	A5	A	A5	
STXXX-XXG-XXX			A1	A
STGXX-XXA-XXX				
SMXXX-XXA-XXX	A1			
SMXXX-XXH-XXX	A5	A		
SIEMENS Transmitters				
7MF433X-XXX0 (4) X-XXXX			A2	A
7MF433X-XXX2 (6) X-XXXX			A1	A
7MF44 (5) 3X-XXX0 (4) X-XXXX	A2			
7MF44 (5) 3X-XXX2 (3, 6, 7) X-XXXX	A1			
7MF44 (5) 3X-XXX1 (5) X-XXXX	A3			

- A: Connecting with fittings
A1: Connecting with flange and sealing rings, using 7/16 - 20 UNF x 1.75" bolts
A2: Connecting with flange and sealing rings, using M10 x 40 mm bolts
A3: Connecting with flange and sealing rings, using M12 x 40 mm bolts
A4: Connecting with flange and sealing rings, using 7/16 - 20 UNF x 3" bolts
A5: Remove the kidney flanges and then connect with flange and sealing rings